

# ABSOLUTE CONCRETE

## Round Ballcock Protected Trough

1 January 2015. Measurements and quantities are approximate. External / Outside measurements shown.



### Featuring:

- Covered Ball Valves for protection.
- Internal pipe fittings with brass elbows either fitted under water or above water to stop back-siphoning, (Backflow), and to permit easy maintenance. All edges are tapered to prevent injury to stock.
- 

Code/Gal.	Litres	Inlet (mm)	Diameter (mm)	Depth (mm)	Weight (kg)
TRB50	227	20	1100	400	350
TRB100SH	455	20	1370	430	560
TRB200SH	910	20	1760	510	890
TRB220CT**	980	20	1510	610	890
TRB300CT	1365	25	1900	610	1126
TRB400CT	1820	25	2170	625	1442
TRB600CT	2730	25	2745	600	1770
TRB800CT	3640	25	2745	700	1880

### \*\* External Ballcock Protector

On this particular trough (TRB220CT) the ballcock protector is moulded on the exterior of the trough as shown in picture above. The external ballcock protector holds approximately 70 litres extra per trough.

# ABSOLUTE CONCRETE

## Trough Dimensions List – Plain and other

1 January 2015. Measurements and quantities are approximate. External / Outside measurements are shown.

### Plain Round Troughs

Code/Gal.	Litres	Inlet (mm)	Diameter (mm)	Depth (mm)	Weight (kg)
TR8	36	20	500	300	60
TR16	73	20	670	300	90
TR45	205	20	930	460	200
TR80	364	20	1090	510	250
TR100SH	455	20	1370	430	440
TR100CT	455	20	1200	520	400
TR120	545	20	1200	615	410
TR160CT	720	20	1370	610	500
TR200SH	910	20	1760	510	660
TR200CT	910	20	1510	610	570
TR250	1137	25	1760	610	780
TR300CT	1365	25	1900	610	920
TR400	1820	25	2170	625	1120
TR600	2730	25	2745	600	1520
TR800	3640	25	2745	750	1830

### Rectangular Troughs

Code/Gal.	Litres	Depth (mm)	Width (mm)	Length (mm)	Weight (kg)
TRO18	82	410	525	675	120
TRO50	227	380	750	1300	250
TRO50E	227	380	750	1300	300
TRO50C	227	380	750	1300	340
TRO80	364	600	700	1830	300
TRO140	587	450	700	2870	450
TRO200	910	450	1300	2870	1050

### Pig Troughs

Code	Depth (mm)	Width (mm)	Length (mm)
TRP3	160	255	900
TRP6	210	300	1800